

US009636087B2

US 9,636,087 B2

May 2, 2017

(12) United States Patent

Miyaki

(54) ULTRASOUND OBSERVATION APPARATUS, METHOD FOR OPERATING ULTRASOUND OBSERVATION APPARATUS, AND COMPUTER-READABLE RECORDING MEDIUM

(71) Applicant: **OLYMPUS CORPORATION**, Tokyo

(JP)

(72) Inventor: Hironaka Miyaki, Hino (JP)

(73) Assignee: **OLYMPUS CORPORATION**, Tokyo

(JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/148,046

(22) Filed: May 6, 2016

(65) Prior Publication Data

US 2016/0242743 A1 Aug. 25, 2016

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2014/078998, filed on Oct. 24, 2014.

(30) Foreign Application Priority Data

Jan. 24, 2014 (JP) 2014-011840

(51) Int. Cl. A61B 8/08

A61B 8/00

(2006.01) (2006.01)

(Continued)

(52) U.S. Cl.

(Continued)

(58) Field of Classification Search

CPC ... A61B 8/5223; A61B 8/5207; A61B 8/5246; A61B 8/463; A61B 8/4461; A61B 8/4477

See application file for complete search history.

(56) References Cited

(10) Patent No.:

(45) Date of Patent:

U.S. PATENT DOCUMENTS

8,619,142 B2 12/2013 Miyaki 2012/0310087 A1 12/2012 Miyaki et al. 2015/0148678 A1 5/2015 Hashiba et al.

FOREIGN PATENT DOCUMENTS

JP 5114609 B2 1/2013 JP 2013-056033 A 3/2013 (Continued)

OTHER PUBLICATIONS

International Search Report dated Feb. 10, 2015 issued in PCT/JP2014/078998.

(Continued)

Primary Examiner — Bo J Peng (74) Attorney, Agent, or Firm — Scully, Scott, Murphy & Presser, P.C.

(57) ABSTRACT

An ultrasound observation apparatus includes: a first generation unit that computes a received signal based on first and second echo signals obtained by transmitting ultrasound signals having different phases along a same line to a specimen and reflection of the ultrasound signals from the specimen, and generates a first ultrasound image having first display mode, using the received signal; an extraction unit that calculates first and second features based on frequency spectra of the first and second echo signals, and extracts a third feature from the first and second features so as to be associated with a pixel position in image; a second generation unit that generates a second ultrasound image having second display mode at a pixel position where the third feature is not less than threshold; and a composition unit that generates a composite image by combining the first and second ultrasound images at the pixel position.

11 Claims, 14 Drawing Sheets

